

# 22" Professional LED Monitor

## Model: KO-LED22A

# KOVO



## Product Features

- **HD: Max 3820\*2160**, 4 times higher than normal monitor.
- Turn on the screen to automatically detect the resolution of the input signal in the upper right corner of the screen.
- Clear: delicate and realistic, conveying true colors, showing the true colors.
- Bright: The quality is improved, only for better presentation.
- Adopt industrial screen, high brightness, high contrast.
- High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work.
- Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture.
- Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology.
- Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
- LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health.
- 5 ms extremely fast response, avoiding the tailing phenomenon of images in high-speed operation.
- Using nanotechnology, the picture is more three-dimensional, transparent.

## Ordering Information

Model	Comment
KO-LED22A	22" Professional LED Monitor

## Product Specifications

**Product type:** Professional Monitor

**Product model:** KO-LED22A

**Screen size:** 22"

**Screen type:** LED

**Screen ratio:** 16:9

**Brightness:** 450nit

**Contrast ratio:** 3000:1

**Response time:** 5 ms

**Visual area:** 478\*278

**Viewing angle:** 160°/ 170°

**Display color:** 16.7M

**Max Resolution:** 1920\*1080/3820\*2160

**Control method:** panel infrared

**Input port:** HDMI, VGA

**Audio output:** 2 stereo speakers

**Power supply mode:** 12V / 4A

**Total power:** 50W

**Case:** professional fireproof iron case

**Product outer dimensions:** 510 \* 315 does not include foot height (foot height 25mm)

**Installation method:** base, wall mount (with 4 \* Hexagonal column screw)

**Product weight:** 2.4kg

**Packing:** (1pcs) 550 \* 430 \* 105 / 3.3kg; (5pcs) 560 \* 440 \* 540 / 17.5kg

**Working environment temperature:** most suitable for 20°C

**Working environment humidity:** 10% - 90% RH

**Storage temperature:** - 20°C ~ 60°C

