



Vandal proof Dome Day & Night IR PW115-I28



Key Features

- **Sensor**
Using high-performance image sensor, with millions of pixels resolution.
- **Auto Gain Control (AGC)**
Built-in auto gain control (AGC) circuit. The color camera can get high-definition picture in low Lux condition.
- **Auto Electronic Shutter (AES)**
Built-in auto electronic shutter function.
- **Gamma Characteristic**
Camera Gamma characteristic is 0.45.
- **Scanning Mode**
NTSC or PAL mode.
- **Night-time Vision**
0 Lux with IR LED ON. Adopt TaiWan high quality IR LED, having very good night-vision effect.

Specifications

Model no.	PW115-I28
Camera	
Pick Up Element	1 / 2.5 FH8538M+K05
Effective Picture Element (H*V)	2560 * 1440, 2560 * 1944
Horizontal Resolution	4MP 5MP
S/N Ratio	More than 48dB
Minimum Illumination	0 Lux (with IR on)
Auto Electronic Shutter	PAL: 1 / 25s-1 / 10000s, NTSC: 1 / 30s- 1 / 10000s
Auto Gain Control	Auto
White Balance	Auto
Day and Night Conversion	ICR mechanical switch
IR Project Distance	20 meters (with 2 Unit infrared LED)
IR Power On	CDS Auto Control
Video Output	AHD/CVI/TVI/CVBS
Power/Current	12VDC (+/-10%)/ 300mA
Lens	2.8mm
Water Resistance	IP66
Dimension (mm)	ø115 x 65
Weight (g)	360
Storage Temperature	-30° ~ +60° C
Operating Temperature	-10° ~ +55° C

Petawise Inc.

Unit 8-9, 1040 Martin Grove Road, Etobicoke, Ontario, Canada M9W 4W1
 Sales@petawise.com; Marketing@petawise.com
 www.petawise.com

**Product specifications and availability are subject to change without notice.*