



## Vandal proof Dome Days & Night IR PW125-I28



### Key Features

- **Sensor**  
Using high-performance image sensor, with millions of pixels resolution.
- **Auto Gain Control (AGC)**  
Built-in auto gain control (AGC) circuit. The color camera can get high-definition picture in low Lux condition.
- **Auto Electronic Shutter (AES)**  
Built-in auto electronic shutter function.
- **Gamma Characteristic**  
Camera Gamma characteristic is 0.45.
- **Scanning Mode**  
NTSC or PAL mode.
- **Night-time Vision**  
0 Lux with IR LED ON. Adopt TaiWan high quality IR LED, having very good night-vision effect.

# Specifications

Model no.	PW125-I28
Camera	
Pick Up Element	1 / 2.5 FH8538M+K05
Effective Picture Element (H*V)	2560 * 1440, 2560 * 1944
Horizontal Resolution	4MP 5MP
S/N Ratio	More than 48dB
Minimum Illumination	0 Lux (with IR on)
Auto Electronic Shutter	PAL: 1 / 25s-1 / 10000s, NTSC: 1 / 30s- 1 / 10000s
Auto Gain Control	Auto
White Balance	Auto
Day and Night Conversion	ICR mechanical switch
IR Project Distance	20 meters (with 12 Unit infrared LED)
IR Power On	CDS Auto Control
Video Output	AHD/CVI/TVI/CVBS
Power/Current	12VDC (+/-10%)/ 250mA
Lens	2.8mm
Water Resistance	IP66
Dimension (mm)	ø110 x 85
Weight (g)	380
Storage Temperature	-30° ~ +60° C
Operating Temperature	-10° ~ +55° C

## Petawise Inc.

Unit 8-9, 1040 Martin Grove Road, Etobicoke, Ontario, Canada M9W 4W1  
 Sales@petawise.com; Marketing@petawise.com  
 www.petawise.com

*\*Product specifications and availability are subject to change without notice.*